

秀 SSU DXO

100% SYNTHETIC MULTIGRADE OIL FOR DIESEL ENGINES

Properties

- ▶ 100% Fully Synthetic.
- ▶ Very high protection against wear, in all conditions of services.
- ▶ Very good viscosity stability in operation.
- ▶ Very high detergency and dispersancy levels (limits oil thickening due to soots).

Performance

- ▶ MB 228.3
- ▶ ACEA E3/E5/E7
- ▶ VOLVO VDS-3
- ▶ API CI-4/CH-4/CG-4
- ▶ MACK EO-M
- ▶ MAN 3275
- ▶ SAE : 10W-40

Uses

- ▶ For all turbocharged or normally aspirated diesel engines of vehicles operating in the most severe conditions whatever the seasons.
- ▶ Responds to the API CI-4 specifications for new low emission engines.
- ▶ Adapted for extended drain intervals.

Characteristics

Property	Unit	10W-40
Density, 15°C	g/cm ³	0.8568
Viscosity, 40°C	mm ² /s	94.767
Viscosity, 100°C	mm ² /s	14.27
Viscosity Index		155
Flash Point	°C	226
Pour point	°C	-37.5
Total Base Number	mgKOH/g	9.70



Super Solution for U



*Enjoyment of Good Car's Long Life & Green Driving
Green Engine Oil Favoring Car & Environment!*

Green Growth Power Satisfying You & the Earth, the SSU opens new future of car engine oil.