



Protection net against worker's accidents



80 Lt Hydraulic independent unit with bomb group / overgear, filter, cooling radiator, 3 points attac.



KNIFE:
to cut until 2 - 3 cm of diameter.

KNIVES CAN BE SUBSTITUTED WITH DISCS AND VICEVERSA IN A QUICK AND EASY WAY.



DISC:
to cut until 6 - 8 cm of diameter.



Electrohydraulic distributor with electric controls.

ADVANTAGES OF THE MECHANIC TRIMMING

- Labour costs reduction
- It favours air and light circulation
- It favours agricultural machines movement
- It allows an uniform application of chemical products on the leaves
- It favours the application of fertilizers and products against grass on the ground
- It has very positive effectson production

TECHNICAL FEATURES

Model	FL500P	FL700P	FL600P	FL800P
Machine weight (Kg)	680	490	360	340
Hydraulic unit weight (with oil) (Kg)	150	150	150	150
Max height of vertical work (hedging) (Mt)	6,5	7	6,5	4,5
Max height of horizontal work (topping) (Mt)	3,8 ÷ 4,6	4	4,5	3,7
Tractor power (Kw)	16	10	9	9
Work ability with disc (ha/h)	1	0,6	0,6	0,6
Work ability with knives (ha/h)	2	1,5	1,5	1,5
Tractor attac	front	front	front	front

Rivenditore autorizzato



COSTRUZIONI MECCANICHE
E APPLICAZIONI TECNOLOGICHE

12051 ALBA (Cn) - ITALY - Reg. Rondò - Tel. 0173 35450 - Fax 0173 35214
www.bmv-italy.com - bmv@bmv-italy.com



GREEN AND DRY TRIMMING MACHINES



Models for
OLIVE TREES
ORCHARDS
CITRUS TREES
HAZELNUT TREES



Model
[**FL500P**]

Model [FL500P]



[FL500P]

N. 5 hydraulic movements:

- Raise - running 3,20 or 4 mt
- Right bar tilting 0 - 90°
- Left bar tilting 0 - 90°
- Right crosswise - running 165 mm
- Left crosswise - running 165 mm

Cutting bars with ø 500 discs

- 5 Discs - 2 mt of works
- 6 Discs - 2,40 mt of works
- 7 Discs - 2,80 mt of works

Model [FL600P]



There can be different combinations between the vertical cutting bar and the top cutting bar.

- Top bar ø 500 discs
- Vertical bar ø 400 discs

[FL600P]

N. 4 hydraulic movements for:

- Diagonal raise - running 1,2 ÷ 1,5 mt
- Vertical Raise - running 0,8 mt
- Cutting bar inclination
- Top inclination 0 - 90°

Model [FL800P]



The "Top" high cutting group can work both vertically and horizontally. It can be equipped with an automatic retractable feeler in front of poles for nets against hail.



[FL800P]

N. 4 hydraulic movements for:

- Raise - running 800 mm
- Crosswise - running 350 mm
- Cutting bar inclination
- Top inclination 0 - 90°
- ø 400 discs

Model [FL700P]



[FL700P]

N. 3 hydraulic movements:

- Raising running 3,20 or 4 mt
- Cutting bar inclination 0 - 90°
- Left crosswise - hydraulic running 350 mm + manually running 500 mm

Narrow Version Model [FL600PS]



[FL600PS]

Raise running:

- Hydraulic: 1,90 mt
- Mechanic: 0,70 mt



1,25 mt

Details [FL800P]

