

Redaelli Wire Ropes



Redaelli Tecna spa
 Stabilimento ed Amministrazione
 Factory and Administration dept.:
 Via Matteotti, 323
 25063 Gardone Val Trompia
 Brescia, Italy
 Tel. +39 030 89171
 Fax +39 030 8917814

Uff. Comm./Commercial dept.:
 Via A. Volta, 16 - P.O. Box 129
 20093 Cologno Monzese
 Milano, Italy
 Tel. +39 02 25307219
 Fax +39 02 25307212
 E-mail: redcom@redaelli.com
 www.redaelli.com

Sede Legale/Registered Office:
 Piazzale Libia, 2
 20135 Milano
 Capitale sociale € 5.463.118,78
 REA Milano 1080570
 Registro Imprese Tribunale Milano,
 Codice fiscale,
 Partita IVA 06247740159

**ATTESTAZIONE DI CONFORMITA'
 ATTESTATION DE CONFORMITE'
 CERTIFICATE OF CONFORMANCE
 KONFORMITÄTSEKLÄRUNG**

15659/09.007

| | |
|---|------------|
| In accordo con le Direttive CEE | 89/392 |
| According the Directive ECC | 91/368 |
| Suivant de la Directive de la CEE | 93/44 |
| Gemass der Kommission der CEE | 93/68 |
| INSPECTION CERTIFICATE TYPE According to UNI EN 10204-2005 | 3.1 |

Spett.le **SEVERSTAL - METIZ**

162600 Ul. 50-LETIYA OKTYABRYA 1/33

162600 CHEREPOVETS VOLOGDA REG. FEDER.RUSSA

| Funi in acciaio, Wire ropes, Cable acier, Stahl seil | | ISO 9001 - IGQ 8802B | |
|--|---|---|--|
| Materiale prodotto in Garanzia di Qualità Manufactured in Quality Assurance | | Fabriqué en Assurance de Qualité Hergestellt in Qualitätssicherung | |
| a) Conferma d'ordine Confirmation | Order confirmation Auftragsbestätigung | | 15659/09 |
| b) Vs ordine Votre commande | Your order Ihre Bestellung | | SPECIFICATION N. 3 |
| c) Posizione Item | Item Position | | 007 |
| d) Identificazione Identification | Serial Nr Fabrik Nr | | 00020/09.002 |
| e) Diametro nominale Diamètre nominal | Nominal diameter Nenndurchmesser | mm | 15.00 |
| f) Formazione Composition | Construction Seilart | | FLEXPACK |
| g) Anima Core Ame Einlage | | | Metallica Steel core Metallique Stahleinlage |
| h) Classe resistenza Classe de resistance | Rope grade Nennfestigkeit | Grade | 2160 |
| i) Materiale Wire finish Revetement Oberfläche der Drähte | | | Zincato ritrafilato Galvanized Galvanizé retrafilé Verzinkt |
| l) Avvolgimento Lay direction and type Sens de cablage Schlagrichtung | | | Parallelo destro Right Lang Lay Lang a droite Gleichschlag rechtsgangig |
| j) Preformazione Preformation | Preformation Vorförmung | | NO NO NON NEIN |
| k) Forza minima di rottura Charge de rupture minimale | Minimun breaking force Mindestbruchkraft | kN | 224 |
| m) Massa nominale Masse nominale | Unit mass Längengewicht | kg/m | 1.09 |
| n) Norma Norme | Specification Bezugnorme | | EN 12305-2 |
| Comunicazioni - Remarques - Remarks - Bemerkungen | | | |
| p) Actual Breaking Force | | kN | 234 |
| q) The actual breaking force refers to the test of one specimen | | | |
| r) Rope diameter | | mm | 15.32 |
| s) Reel nr. 2 - Net Weight: 1632 kg - Length: 1500 m | | | |
| t) u) v) | | | |

Gardone V.T. (BS) - ITALY

9 settembre 2009

Responsabile Controllo Qualità
 Contremaitre Control de Qualité
 Quality Control Responsible
 Der Leiter Qualitätswesen

G. De Caminata

