

DRAGON TURBO BEST 15W-40



Multigrade oil for Diesel engines

USES

- For all turbocharged or normally aspirated diesel engines of vehicles operating in the most severe conditions whatever the seasons.
- Adapted for extended drain intervals. (up to 45,000km according to manufacturers)
- Particularly suited for lubrication of low emission engines.

PROPERTIES

- Multigrade
- Very high viscosity index
- Excellent viscosity stability in operation
- Exceptional antiwear and anticorrosion properties
- Good efficiency against bore polishing
- Exceptional detergency level
- Very high dispersancy level
- Very good antioxidant, antirust, anti-foaming properties

SPECIFICATION

- MB 228.3/229.1
- VOLVO VDS
- API CI-4
- ACEA E3
- MAN M 3275
- MTU OIL TYPE-2
- ALLISON C4

CHARACTERISTICS

| Test Items | Method | Unit | SAE grade 15W-40 |
|--------------------------|-------------|--------------------------|------------------|
| Specific Gravity 15/4 °C | ASTM D 1298 | - | 0.861 |
| Viscosity 40 °C | ASTM D 445 | mm ² /s (cSt) | 104.4 |
| 100 °C | | mm ² /s (cSt) | 14.7 |
| Viscosity Index | ASTM D 2270 | - | 146 |
| Flash Point | ASTM D 92 | °C | 228 |
| Pour Point | ASTM D 97 | °C | -38 |

Above characteristics are mean values given as an information.

S-OIL TOTAL LUBRICANTS CO., LTD.
 (3F, Ace Tower, Sunwha-dong)
 3F, 92 Tongil-ro, Jung-gu, Seoul, Korea
 1/1

S-OIL DRAGON TURBO BEST 15W-40
 2014-07-08



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
 A material safety data sheet is obtainable via your commercial adviser.