

PLH 28 XE | 3 kg L-shape SDS-plus hammer

Article: 4933446800



- Hardest hitting corded SDS hammer in its class. Tough, durable hammer with excellent drilling performance in concrete from the high torque motor and gears and a 4.8 joule single blow energy.
- 800 watt motor combined with optimised drilling speed results in unsurpassed drilling performance.
- Low vibration 10.6 m/s² due to patented dual anti-vibration* handle.
- Good balance and easy handling from the compact L-shape design with dual patented AVS (Anti-Vibration-System) and soft grip handle.
- Reliable safety clutch protects machine and user.
- Roto-stop and variolock for maximum control when doing light chiselling work.
- XE version comes with fast changing FIXTEC adaptor and 13 mm keyed chuck.

	PLH 28 XE
Sound pressure level (dB(A))	90.5
Sound pressure level uncertainty (dB(A))	3
Sound power level (dB(A))	101.8
Sound power level uncertainty (dB(A))	3
Vibration chiselling uncertainty (m/s ²)	1.5
Vibration drilling into concrete uncertainty [m/s ²]	1.5
No load speed (rpm)	0 - 1500
Supplied in	Kitbox
Vibration drilling (m/s<special id="27"/>)	10.6
Vibration chiseling (m/s<special id="27"/>)	6.8
Article Number	4933446800
Weight (kg)	3.6
Power input (W)	800
Max. drilling steel (mm)	13
Max. drilling wood (mm)	40
Max. drilling concrete (mm)	28
Full load hammer action (bpm)	0 - 4000
Full load speed (rpm)	0 - 1000
Blow energy (EPTA)(J)	4.8