



## Stronger Power & Smooth Feeling - Meet the **Dragon!**

# DRAGON SN

### Properties

- ▶ Meets API SN and ILSAC GF-5 requirements, guarantee of a high and constant quality for lubricants.
- ▶ Ensures easy cold start due to its extreme fluidity at low temperature and maintains a very resistant oil film even at high operating temperature.
- ▶ Gives the engine an excellent wear protection, develops performance and power.
- ▶ Reduces friction due to 0W-20 and 5W-20, low viscosity grades and therefore creates fuel savings, which decrease CO2 emissions.
- ▶ Synthetic blended.

### Performance

- ▶ 0W-20, 5W-20, 5W-30, 10W-30 : API SN / ILSAC GF-5, RC (Resource Conserving)
- ▶ 5W-40, 10W-40 : API SN
- ▶ SAE : 0W-20, 5W-20, 5W-30, 5W-40, 10W-30, 10W-40

### Uses

- ▶ Recommended for all Gasoline engines, specially for most recent technology engines (multi valve, turbocharged, with or without catalytic converter), supercharged or not, in cars.
- ▶ Suitable for all journeys (in town, on highways or motorways) and particularly in severe conditions.
- ▶ For all driving styles, particularly "vigorous" and high speeds.
- ▶ 5W-30, 5W-40, 10W-30, 10W-40 are also suitable for LPG vehicles.

### Characteristics

Property	Unit	0W-20	5W-20	5W-30	5W-40	10W-30	10W-40
Density, 15°C	g/cm <sup>3</sup>	0.8480	0.8617	0.8615	0.8522	0.8706	0.8696
Viscosity, 40°C	mm <sup>2</sup> /s	46.36	48.80	64.25	87.56	68.20	96.89
Viscosity, 100°C	mm <sup>2</sup> /s	8.70	8.57	10.91	14.19	10.50	14.39
Viscosity Index		169	154	162	168	142	153
Flash Point	°C	204	212	220	214	218	212
Pour point	°C	-43	-33	-33	-33	-30	-33
Total Base Number	mgKOH/g	7.70	7.00	7.06	6.93	7.05	6.95

