

M18 CHM

M18 FUEL™ 5 kg SDS-Max drilling and breaking hammer

Features

- The world's first 18V 5 kg SDS-Max hammer for maximum versatility and portability with equal performance to an AC tool
- Milwaukee® designed and built brushless POWERSTATE™ motor provides corded drilling performance
- New REDLINK PLUS™ intelligence system delivers the most advanced digital overload protection for tool and battery and uniquely enhances the tools performance under load
- High demand 9.0 Ah REDLITHIUM-ION™ battery pack delivers up to 5x more run time, up to 35% more power, up to 2x more battery life and operates better down to -20°C than other lithium-ion technologies
- Robust magnesium gear housing for tough environments, exact seat fitting of gear components and better cooling
- Roto-stop and multi position chisel function gives 12 different positions to optimise working angle and end-user ergonomics
- Low 10.6 m/s² vibration construction which enhances usage time per day
- Safety clutch protects operator and machine if drill bit jams





Nothing but **HEAVY DUTY.**

| RANGE SPEC (1) | M18 CHM-0C | M18 CHM-902C |
|---|-------------------|---------------------|
| No load speed (rpm) | 0 - 450 | 0 - 450 |
| Voltage (V) | 18 | 18 |
| Battery pack capacity (Ah) | - | 9.0 |
| Battery type | Li-ion | Li-ion |
| Optimised drilling capacity in concrete (mm) | ø 16 - 32 | ø 16 - 32 |
| Supplied in | Kitbox | Kitbox |
| Charger supplied | - | 95 min |
| No. of batteries supplied | 0 | 2 |
| Vibration drilling (m/s<special id ="27" />) | 10.6 | 10.6 |
| Vibration chiseling (m/s<special id ="27" />) | 9.6 | 9.6 |
| Max. drilling core bit (mm) | 100 | 100 |
| Max. drilling tunnel bit (mm) | 65 | 65 |
| Weight with battery pack (kg) | - | 6.6 |
| Max. drilling concrete (mm) | 40 | 40 |
| Full load hammer action (bpm) | 0 - 3000 | 0 - 3000 |
| Blow energy (EPTA)(J) | 6.1 | 6.1 |