

Conext™ XW inverter/charger (230 V / 50 Hz)

One solution for global power

Conext XW is an adaptable pure sine wave, single-phase and three-phase inverter/charger system with global grid-tie functionality and dual AC power inputs. Available solar charge controllers, monitoring, and automated generator control modules enable further adaptability. From single Conext XW unit to multiple clusters of units, up to 36 kW each, the Conext XW is a scalable system that allows for the integration of solar capacity as required.

Adaptable and scalable, the Schneider Electric™ Conext XW system is the one solution for global grid-interactive and off-grid, residential and commercial, solar and backup power applications.

Why choose Conext XW (230 V / 50 Hz)?



True bankability

- Warranty from a trusted partner with over 177 years of experience
- World leader in industrial power drives, UPS and electrical distribution
- Strong service infrastructure worldwide to support your global needs



Higher return on investment

- Harness the continuously declining production cost of solar power
- Hybrid integration of generator reduces diesel fuel costs



Designed for reliability

- Robust design through rigorous reliability testing (HALT)
- Proven field performance: 7 years with high reliability, globally in multiple applications and environments



Flexible

- Adapts to single and three-phase systems
- Scales to 36 kW for commercial or large electrification installations
- Supports DC coupled and AC coupled solutions



Easy to service

- Remote monitoring and configuration
- Replaceable boards and components
- Global support



Easy to install

- Devices configure quickly into a stylish wall mounted system
- Inverters connect both grid and generator power with dual AC input



Product applications



Residential, backup power and grid-tie



Off-grid solar



Community electrification



Small commercial, backup power and grid-tie

Device short name	XW4024 230 50	XW4548 230 50	XW6048 230 50
Electrical specifications			
Output power (continuous) at 40°C	4.0 kVA	4.5 kVA	6.0 kVA
Output power (surge) at 40°C	8.0 kVA (20 sec)	9.0 kVA (15 sec)	12.0 kVA (15 sec)
Output current	17.4 A	19.6 A	26.1 A
Peak output current (rms)	35 A	40 A	53 A
Input current at rated power	178 A	96 A	131 A
Type of signal	True sine wave	True sine wave	True sine wave
Automatic transfer relay	56 A	56 A	56 A
Typical transfer time	8 ms	8 ms	8 ms
DC input voltage (nominal)	25.2 V	50.4 V	50.4 V
Input voltage limits	20 to 32 V	40 to 64 V	40 to 64 V
Charging current	150 A	85 A	100 A
Power factor corrected charging	0.98	0.98	0.98
Auxiliary relay output	0 to 12 V, maximum 250 mA DC	0 to 12 V, maximum 250 mA DC	0 to 12 V, maximum 250 mA DC
Power consumption (search mode)	< 7 W	< 7 W	< 7 W
AC input voltage (nominal)	230 V +/- 3%	230 V +/- 3%	230 V +/- 3%
Input voltage limits (bypass/charge mode)	165 to 280 V (230 V nominal)	165 to 280 V (230 V nominal)	165 to 280 V (230 V nominal)
Frequency	50 Hz +/- 0.1 Hz	50 Hz +/- 0.1 Hz	50 Hz +/- 0.1 Hz
AC input frequency range (bypass/charge mode)	40 to 68 Hz (50 Hz nominal)	40 to 68 Hz (50 Hz nominal)	40 to 68 Hz (50 Hz nominal)
Total harmonic distortion (THD)	< 5% at rated power	< 5% at rated power	< 5% at rated power
AC connections	AC1 (Grid), AC2 (Generator)	AC1 (Grid), AC2 (Generator)	AC1 (Grid), AC2 (Generator)
AC input breaker	60 A single-pole	60 A single-pole	60 A single-pole
Efficiency			
Peak	94.0%	95.6%	95.4%
General specifications			
IP degree of protection	IP20 (sensitive electric components sealed inside enclosure)		
Product weight	52.5 kg (116.0 lb)	53.5 kg (118.0 lb)	55.2 kg (121.7 lb)
Shipping weight	74.0 kg (163.0 lb)	75.0 kg (165.0 lb)	76.7 kg (169.0 lb)
Product dimensions (H x W x D)	58 x 41 x 23 cm (23 x 16 x 9 in)	58 x 41 x 23 cm (23 x 16 x 9 in)	58 x 41 x 23 cm (23 x 16 x 9 in)
Shipping dimensions (H x W x D)	71.1 x 57.2 x 39.4 cm (28.0 x 22.5 x 15.5 in)	71.1 x 57.2 x 39.4 cm (28.0 x 22.5 x 15.5 in)	71.1 x 57.2 x 39.4 cm (28.0 x 22.5 x 15.5 in)
Device mounting	Wall mount (backplate included)		
Ambient air temperature for operation	-25°C to 70°C (-13°F to 158°F) (power derated above 45°C (113°F))		
System network and remote monitoring	Available		
Warranty (Depending on the country of installation)	2 or 5 years		
Part number	865-1045-61	865-1040-61	865-1035-61
Features and options			
Display type	Status LEDs indicate AC In status, faults/warnings, equalize mode, On/Off and equalize button battery level. Three-character display indicates output power or charge current		
Supported battery types	Flooded (default), Gel, AGM, custom		
Battery bank size	100 to 2000 Ah (scaled to PV array size)		
Battery temperature sensor	Included		
Non volatile memory	Yes		
Multiple unit configurations	Single-phase: up to four parallel units. Three-phase: two units per phase		
Regulatory approval			
CE marked according to the following EU directives and standards:			
EMC directive	EN61000-6-1, EN61000-6-3, EN61000-3-2, EN61000-3-3		
Low voltage directive	EN50178		
RCM marked and compliant	AS 4777.2, AS 4777.3, AS/NZS 3100		

Specifications are subject to change without notice.

Conext XW works with the following Schneider Electric products



XW Power Distribution Panel
Product no. 865-1015



XW Connection Kit
Product no. 865-1020



System Control Panel
Product no. 865-1050



Automatic Generator Start
Product no. 865-1060



MPPT 60 150 solar charge controller
Product no. 865-1030-1



MPPT 80 600 solar charge controller
Product no. 865-1032



XW Configuration Tool
Product no. 865-1155



**Conext Combox
Communication device**
Product no. 865-1058