

MITAS TS - 04

Product detail



TS-04 / 6.00-16

Traction tread pattern with excellent traction.

TYRE SIZE	TREAD PATTERN	PR	LI / SS FR / DW	SS	TYPE	RIM (PERMITTED)	TUBE / FLAP	OD	SW	SR	RC	FR	DW	INFLATION (kPa)
6.00-16	TS-04	6	91/79	A8	TT	4.50Ex16 (4.00Ex16)	6.00-16	735	169	345	2160	615	437	275
6.00-16	TS-04	8	100/88	A8	TT	4.50Ex16 (4.00Ex16)	6.00-16	735	169	345	2160	800	560	400

TS-04 / 7.50-16

TYRE SIZE	TREAD PATTERN	PR	LI / SS FR / DW	SS	TYPE	RIM (PERMITTED)	TUBE / FLAP	OD	SW	SR	RC	FR	DW	INFLATION (kPa)
7.50-16	TS-04	6	100/88	A8	TT/TL	5.50Fx16 (5.00F,6.00F)	7.50-16	803	205	375	2360	800	560	225
7.50-16	TS-04	8	108/95	A8	TT/TL	5.50Fx16 (5.00F,6.00F)	7.50-16	803	205	375	2360	1000	690	325