

# DAILY RG9000KS

# GENMAC



**MADE IN ITALY**

Picture as a way of example only

MODEL	DAILY RG9000KS
<b>ALTERNATOR</b>	
Type Voltage - Frequency Prime Power Max. Power Intensity PRP / LTP Protection	Synchronous, single phase, brushless, Self Regulated, Self Excited 230V - 50 Hz 8,8 kW / 9,8 kVA 9,8 kW/10,9 kVA 38,3 A / 42,6 A IP 23
<b>ENGINE</b>	
Type Brand Model Displacement - HP Fuel Autonomy/ Fuel tank Starting System	Twin -Cylinder, 4 Strokes, air cooled, 3000 rpm KOHLER KD 425/2 851 cc / 20 DIESEL 8 h / 19 lt. <b>ELECTRICAL (battery included)</b>
Control Panel     Dimensions mm LxLxA Weight - Kgs. Noise Level @7m.	Socket 1x CEE 16A 230V; 2x CEE 32A 230V Thermal breaker, Circuit Breaker, Voltmeter (analogic), Analogic hourmeter h, Start/Stop switch, Emergency stop button, 10 PIN sochett for remote strat - presetting for ATS connection. Engine Protection card RGK30: Low oil presure protection, High temperature protection, over/under speed protection, charger alternator failurenprotection. Battery.